



➔ Full Height Turnstile

Power Supply : 100V ~ 240V AC
 Control Circuit : 24V DC
 Power Consumption : 30W
 Operating Temper range : -25°C ~ +70°C
 Protection level (IP) : ≥ 44
 Humidity : 95%
 Hydraulic damper : Adjustable
 Solenoid : 24V DC 100%
 Throughout : Person
 Signal Output : 12V Pulse
 Communication Interface : RS485 or TCP IP
 Passage width : ≤ 650mm
 Frequency : ≤ 50Hz or 60Hz
 Electro-magnetic drive : DC
 Section version : 120 degree
 No of arms : 3 arms
 Dimensions : 1630 x 1500 x 2310 mm

Feature :

- ▶ Designed for secure operation wish aesthetics inland
- ▶ Corrosion protected S/S frame
- ▶ Minimal exposed hardware
- ▶ Heavy Gauge materials ASTM Standard
- ▶ Consists of rotor assembly, shield
- ▶ Assembly, barrier section, mechanism housing & ceiling plate
- ▶ The barrier can be set to delay closing in 1 ~ 60s after a valid card reading
- ▶ Single passage in the set direction
- ▶ Bi-directional single passage
- ▶ Free passage in the direction
- ▶ Always free or locked